



U Bolt Mechanical Tee VAT09U

The Model **VAT09U** Saddle-Lets is the ideal outlet fitting for direct connections to sprinkler heads, drop nipples, and or gauges. No need for welding, just cut or drill a hole at the desired outlet location. Position the Saddle-Let so that the locating collar fits within the hole and is secure with the U-bolt and nuts. The Saddle-Let comes with a standard black finish or as an option can be supplied electro-zinc plated or painted orange. The Saddle-Let allows full bore flow and pressure rates to 300 psi (20 bar).



U Bolt Mechanical Tee

Nominal Size	Pipe O.D.	Working Pressure	Hole Dia	Dimensions			Bolt Size
mm/in	mm/in	psi/Mpa	Mm/in	mm/in			No. –Size mm
				A mm	B mm	C mm	
25 × 15 1 × 1/2	33.7 × 21.3 1.327 × 0.825	300Psi 2.07Mpa	20 0.79	35 1.38	80 3.15	56 2.2	M10 × 33U
25 × 20 1 × 3/4	33.7 × 26.9 1.327 × 1.050		20 0.79	40 1.57	80 3.15	56 2.2	M10 × 33U
32 × 15 1 1/4 × 1/2	42.4 × 21.3 1.660 × 0.825		30 1.18	43 1.69	90 3.54	56 2.2	M10 × 42U
32 × 20 1 1/4 × 3/4	42.4 × 26.9 1.660 × 1.050		30 1.18	43 1.69	90 3.54	56 2.2	M10 × 42U
32 × 25 1 1/4 × 1/2	42.4 × 33.7 1.660 × 1.315		30 1.18	51 2.01	90 3.54	56 2.2	M10 × 42U
40 × 15 1 1/2 × 1/2	48.3 × 21.3 1.900 × 0.825		30 1.18	46 1.81	90 3.54	56 2.2	M10 × 48U
40 × 20 1 1/2 × 3/4	48.3 × 26.9 1.900 × 1.050		30 1.18	46 1.81	90 3.54	56 2.2	M10 × 48U
40 × 25 1 1/2 × 1	48.3 × 33.7 1.900 × 1.315		30 1.18	54 2.13	90 3.54	56 2.2	M10 × 48U
50 × 15 2 × 1/2	60.3 × 21.3 2.375 × 0.825		30 1.18	52 2.05	96 3.78	56 2.2	M10 × 60U
50 × 20 2 × 3/4	60.3 × 26.9 2.375 × 1.050		30 1.18	52 2.05	96 3.78	56 2.2	M10 × 60U
50 × 25 2 × 1	60.3 × 33.7 2.375 × 1.315		30 1.18	60 2.36	96 3.78	56 2.2	M10 × 60U
65 × 15 2 1/2 × 1/2	73 × 21.3 2.874 × 0.825		30 1.18	60 2.36	112 4.41	56 2.2	M10 × 73/76U
65 × 20 2 1/2 × 3/4	73 × 26.9 2.874 × 1.050		30 1.18	60 2.36	112 4.41	56 2.2	M10 × 73/76U
65 × 25 2 1/2 × 1/2	73 × 33.7 2.874 × 1.315		30 1.18	68 2.68	112 4.41	56 2.2	M10 × 73/76U
65 × 15 2 1/2 × 1/2	76.1 × 21.3 3.000 × 0.825		30 1.18	60 2.36	112 4.41	56 2.2	M10 × 73/76U
65 × 20 2 1/2 × 3/4	76.1 × 26.9 3.000 × 1.050		30 1.18	60 2.36	112 4.41	56 2.2	M10 × 73/76U
65 × 25 2 1/2 × 1/2	76.1 × 33.7 3.000 × 1.315		30 1.18	68 2.68	112 4.41	56 2.2	M10 × 73/76U
80 × 15 3 × 1/2	88.9 × 21.3 3.500 × 0.825		38 1.50	70 2.76	144 5.67	74 2.91	M12 × 89U
80 × 20 3 × 3/4	88.9 × 26.9 3.500 × 1.050		38 1.50	70 2.76	144 5.67	74 2.91	M12 × 89U
80 × 25 3 × 1	88.9 × 33.7 3.500 × 1.315		38 1.50	75 2.95	144 5.67	74 2.91	M12 × 89U

Datas are for reference only.