


Grooved Concentric Reducer VAT11

VAN-TEC concentric reducer is cast of ductile iron. The end-to-end dimensions of these reducers are less than that of fabricated reducers.



Grooved Concentric Reducer

Nominal Size	Pipe O.D.	Working Pressure	Dimensions
mm/in	mm/in	psi/Mpa	L mm/in
32 x 25 1 1/4 x 1	42.4 x 33.7 1.660 x 1.315	300Psi 2.07Mpa	64 2.51
40 x 25 1 1/2 x 1	48.3 x 33.7 1.900 x 1.315		64 2.51
40 x 32 1 1/2 x 1 1/4	48.3 x 42.4 1.900 x 1.660		64 2.51
50 x 25 2 x 1	60.3 x 33.7 2.375 x 1.315		64 2.51
50 x 32 2 x 1 1/4	60.3 x 42.4 2.375 x 1.660		64 2.51
50 x 40 2 x 1 1/2	60.3 x 48.3 2.375 x 1.900		64 2.51
65 x 25 2 1/2 x 1	73.0 x 33.7 2.875 x 1.315		64 2.51
65 x 32 2 1/2 x 1 1/4	73.0 x 42.4 2.875 x 1.660		64 2.51
65 x 40 2 1/2 x 1 1/2	73.0 x 48.3 2.875 x 1.900		64 2.51
65 x 50 2 1/2 x 2	73.0 x 60.3 2.875 x 2.375		64 2.51
65 x 32 2 1/2 x 1 1/4	76.1 x 42.4 3.000 x 1.660		64 2.51
65 x 40 2 1/2 x 1 1/2	76.1 x 48.3 3.000 x 1.900		64 2.51
65 x 50 2 1/2 x 2	76.1 x 60.3 3.000 x 2.375		64 2.51
80 x 32 3 x 1 1/4	88.9 x 42.4 3.500 x 1.660		55 2.17
80 x 40 3 x 1 1/2	88.9 x 48.3 3.500 x 1.900		55 2.17
80 x 50 3 x 2	88.9 x 60.3 3.500 x 2.375		55 2.17